





rotomotive
looks good. performs better.




REVVO IE2/IE3/IE4

3 Phase Energy Efficient
Induction Motors




REVVO ATDC/ATAC

ATDC / AT24 Break Motors




REVVO Exd

Flame Proof Motors




REVVO CR

Crane Duty Motors



REVVO DELFIRE


Smoke & Heat Exhaust
Ventilation Motors



REVVO PM IE5

Energy Efficient Motors

REVVO Series | 3 Phase Energy Efficient Induction Motors



ENERGY EFFICIENT IE2, IE3 & IE4 MOTORS

Revvo series energy efficient asynchronous squirrel cage induction motors – high efficiency IE2 & premium efficiency IE3 & Super premium efficiency IE4 are manufactured conforming to IEC-60034-30/IS 12615.


Rating & Frame size	Voltage	Frequency	Duty	Insulation	Protection
0.12 kW to 315 kW 2, 4 & 6 pole 63 to 355L frame	Suitable for multiple voltage	50 / 60 Hz	S1	F class (H class on request)	IP55 (IP56, IP66 on request)

REVVO ATDC / AT24 / ATAC MOTORS

- Self-braking motor series
- Electromagnetic type brake coil normally OFF
i.e. the braking action occurs in the absence of power supply

Rating & Frame size	Revvo ATDC	Revvo AT24	Revvo ATAC	Brake Insulation
0.12 kW to 22 kW 2, 4, 6 & 8 pole 63 to 180L frame	104/180 Volt DC input to brake through built in rectifier	24 Volt DC input to brake through an inverter	415 Volts AC input to brake	H Class

ATDC / AT24



REVVO Exd SERIES FLAME PROOF MOTORS


- Manufactured as per IS/IEC 60079-1 for operation in hazardous locations classified as zone 1 and zone 2 area as per IS:5572
- Suitable for Gas Group -2 (for equipment other than mines)
- Suitable for temperature class T4, T5 & T6

Rating & Frame size		
0.37 kW to 18.5 kW	2, 4 & 6 pole	80 to 160L frame

REVVO CR – CRANE DUTY MOTORS



- Revvo CR series motor used in cranes and hoists
- Typically in one frame size lower than S1 duty motors
- Conforms to IS:12615

Rating & Frame size	Duty	Brake
0.37 kW to 22 kW 4 & 6 pole 71 to 160L frame	S3/S4/S5 capable for frequent starts/stops and reversals	Can be supplied with DC, 24 V DC and AC brake



- B3, B5 and B14 mounting
- VPI impregnation
- Steel insert in bearing seats (from frame size 80)
- 6 terminals – run same motor in Star or Delta
- Lightweight die-cast Aluminium construction (upto 132 frame)

- Optional fine balancing Grade 2.5
- Suitable for 50°C ambient
- Service factor 1.1 with class F temperature rise
- Conforms to IS 12615
- Patented Design • CE Mark



Flexible Terminal Box Positions (63 o 132 frame)

REVVO Delfire | Smoke & Heat Exhaust Ventilation Motors




Revvo Delfire series of motors are designed to be a part of smoke and heat control ventilation system. They are also used with jet fans to exhaust smoke, NOx or other gases from tunnels, car parks, areas and other enclosed spaces. These motors are guaranteed to operate continuously for a period of up to 2 hours and at temperatures of up to 400°C. Delfire motors are available in single or dual speed configurations and are compliant to EN 12101.


Rating & Frame size	Voltage & Frequency	Duty	Insulation	Protection
0.12kW to 90 kW 2,4,6 and 8 pole 63 frame 280 frame	Suitable for multiple voltage	S1	H class	IP55 (IP56, IP66 on request)

REVVO PM IE5 | Energy Efficient Motors


The Permanent Magnet Synchronous Motor (PMSM) is an AC synchronous motor whose field excitation is provided by permanent magnets, and has a sinusoidal back EMF waveform. The PMSM is a cross between an induction motor and brushless DC motor. With permanent magnets the PMSM can generate torque at zero speed; it requires digitally controlled inverter for operations. PMSM are typically used for high-performance and ultra premium-efficiency (IE5) motor drives.



- High air gap flux density
- High power-to-weight ratio
- Large torque-to-inertia ratio
- Smooth torque operation (also at low speeds)
- Accurate torque control at zero speed
- High-speed operation
- High overloading torque
- High efficiency and high power factor
- 0.37kW to 90kW, 4 pole and 6 pole, 80 to 280 frame
- S1 duty, IP55 as standard feature




REVVO IE2 INDUCTION MOTOR



Savings @ ₹9402

& payback 3 months
(Comparison between IE2-IE1*)


REVVO IE3 /IE4 INDUCTION MOTOR



Savings @ ₹6009

& payback 4.3 months
(Comparison between IE4-IE2*)


REVVO IE5 PMSM MOTOR



Savings @ ₹11446

& payback 4.0 months
(Comparison between IE5-IE2*)



Efficiency Comparison*



* For 5.5kW-4 pole motor



BUSINESS ALLIANCE WITH ORANGE1 GROUP - ITALY



rotomotive
looks good. performs better.

Authorised Dealer

Rotomotive Powerdrives India Ltd.

223, Napa Talpad, Gana-Borsad Road, Tal: Borsad, Anand-388560, Gujarat, India

Ph.: +91-9227110010/20/30 Fax: +91-2692-235209 Email: info@rotomotive.com • www.rotomotive.com